

LED Industrial Light

**CE & RoHS Certified LED Floodlight/bay light/platform light
in Industrial Area.**

Forest Frog Series

CE RoHS

www.khjled.com



Features And Benefits:

- High efficacy LED Source with long lifespan, L70 > 100,000 hours @ 25°C ambient
- 5-year performance warranty
- Low THD around 10%, Less interference
- 5KV Surge Protection
- Robust aluminium housing and strong tempered glass
- Vibration and shock resistant
- Low maintenance

Applications:



Cement plants



Warehouse



Factory



Power Generation



Power Transmission



Shipping industry

CE RoHS

CE & RoHS Certified LED Floodlight/bay light/platform light in Industrial Area.

LED Floodlight/bay light/platform light

Standard & Certificate:

Certificate:	• CE • RoHS
Executive Standard:	• EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3 • EN 60598-1, EN 60598-2-5, EN 62031, EN 62493 • IEC 62321-4, IEC 62321-5, IEC 62321-6 • IEC 62321-7-1, IEC 62321-7-2, IEC 62321-8

Electrical & Photometric Features:

Luminaire Efficacy:	136.5lm/W
Lifespan:	>100,000 hours
Operating Voltage:	100-277 VAC 141-392 VDC/24 VDC
Power(W):	12W/24W/35W
Frequency:	50/60Hz
Power Factor:	>0.98
THD:	<10%
Insulation Class:	I
Surge Protection:	5KV
LED Driver:	Over voltage protection/short circuit protection


Mechanical Features:

Weight:	2.4Kg(Junction box),2.6Kg(Stanchion junction box)
Size:	φ 136*210mm(Junction box), φ 136*194mm(Stanchion junction box)
Ambient Temperature:	-40℃~+55℃
Connecting Terminals:	3*1.0-4mm ² (L+N+PE)
Cable Entries:	1XNPT 3/4" (M20*1.5, M25*1.5 are optional)
Earthing Protection:	M4 (Internal & external earth bolts)
IP Code:	IP66
Enclosure Material:	Die-casting aluminium alloy
Enclosure Colour:	Grey RAL7040
Coating:	Epoxy powder coating
Exposed Fastener:	Stainless steel
Protective Cover:	Tempered glass,Stand 7J impact

CE RoHS

CE & RoHS Certified LED Floodlight/bay light/platform light in Industrial Area.

Production Definition




Ordering Information


P/N	Operating Voltage(V)	Luminous Flux(lm)	Power(W)	CRI	Color Temp.	CCT(K)
KFIF12H6V6WM-*-E	100~277 AC (141~392 DC)	1512	12	80	Warm white	3000±300
KFIF12H6V6NH-*-E		1638	12	70	Natural white	4000±300
KFIF12H6V6NH-*-E		1638	12	70	Natural white	5000±300
KFIF12H6V6CH-*-E		1638	12	70	Cool white	5700±300
KFIF24H6V6WM-*-E		3024	24	80	Warm white	3000±300
KFIF24H6V6NH-*-E		3276	24	70	Natural white	4000±300
KFIF24H6V6NH-*-E		3276	24	70	Natural white	5000±300
KFIF24H6V6CH-*-E		3276	24	70	Cool white	5700±300
KFIF35H6V6WM-*-E		4410	35	80	Warm white	3000±300
KFIF35H6V6NH-*-E		4778	35	70	Natural white	4000±300
KFIF35H6V6NH-*-E		4778	35	70	Natural white	5000±300
KFIF35H6V6CH-*-E		4778	35	70	Cool white	5700±300

Remarks: *Stands for product type, including J, J1A, J1B, J1C, J1D

Candela Distribution




H6V6(120°)/High efficacy LED Source




Installation Method


Ceiling Mount:




BR-FIF-G



Pipe Mount:



PCR-FF



Optional Parts

No.	Installation accessories	Part No.	Picture	Material	Weight(Kg)	QTY	Remark
1	Bracket	BR-FIF-G		Q235	0.4	1	Ceiling mount
2	Pipe connector	PCR-FF-N PCR-FF-M		SUS304	0.28	1	Pipe mount