



LED Explosion Proof Light

**ATEX & IECEx Certified LED Linear light in Hazardous Area.
Swordfish Series**

- ⚡ II 2 G Ex d eb op is IIB T6 Gb
- ⚡ II 2 D Ex tb op is IIIC T80°C Db





Features And Benefits:

- High efficacy LED Source with long lifespan, L70 > 100,000 hours @ 25°C ambient
- 5-year performance warranty
- Low THD around 10%, Less interference
- 4KV/Line-Line 6KV/Line-Earth
- Robust aluminium housing and strong tempered glass
- Vibration and shock resistant
- Low maintenance

Applications:



Oil&Gas Exploration



Drilling



Oil Refinery



Petrochemical Plant



Power Plant



Pharmaceutical Plant



ATEX & IECEX Certified LED Linear light in Hazardous Area.

LED Linear light

Standard & Certificate:

Ex Mark:	Gas: II 2 G Ex d eb op is IIB T6 Gb Dust: II 2 D Ex tb op is IIIC T80°C Db
Certificate:	• ATEX Certification NO.: TÜV 15 ATEX 7673 X • IECEx Certification NO.: IECEx TUR 16.0028X • CE • ABS • RoHS
Executive Standard:	• (IEC)EN 60079-0, (IEC)EN 60079-1, (IEC)EN 60079-7, • (IEC)EN 60079-28, (IEC)EN 60079-31 • EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3, EN 60598-1, • EN 60598-2-5, EN 62031, EN 62493, • IEC 62321-4, IEC 62321-5, IEC 62321-6, IEC 62321-7-1, • IEC 62321-7-2, IEC 62321-8
Classification:	• Group II Zone 1 & 21 and 2 & 22

Electrical & Photometric Features:

Luminaire Efficacy:	136.5lm/W
Lifespan:	>100,000 hours
Operating Voltage:	100-277 VAC/24-48 VAC 10-30 VDC/24-48 VDC/141-392 VDC
Power(W):	18W/36W/48W(0.6m), 36W/48W/56W/72W(1.2m)
Frequency:	50/60Hz
Power Factor:	>0.98
THD:	<10%
CRI:	>70
Insulation Class:	I
Surge Protection:	4KV/6KV
LED Driver:	Over voltage protection/short circuit protection

Mechanical Features:

Weight:	6.9Kg(0.6m)/11.5Kg(1.2m)
Size:	600*136*124mm(18W/36W/48W)/1200*136*124mm(36W/48W/56W/72W)
Ambient Temperature:	-20°C~+55°C
Connecting Terminals:	3*1.0-4.0mm ² (L+N+PE)
Cable Entries:	2XNPT 3/4" (M20*1.5, M25*1.5 are optional)
Earthing Protection:	M4 (Internal & external earth bolts)
IP Code:	IP66
Enclosure Material:	Copper-free Aluminium
Enclosure Colour:	Grey RAL7040
Coating:	Epoxy powder coating
Exposed Fastener:	Stainless steel
Protective Cover:	Tempered glass, Stand 7J impact



ATEX & IECEx Certified LED Linear light in Hazardous Area.

Production Definition


Ex	K	SF	XX	XX	XX	XX	XX	-U	-E	-X
Type	Brand	Series	Power	Input Voltage	Length	Candela Distribution	CCT(K)	Type	Area	Color
Ex-Explosion Proof	K-KHJ	SF-Swordfish series	18-18W 36-36W 48-48W 56-56W 72-72W	Default-100-277VAC A-24-48VAC/DC B-10-30VDC	600-600mm 1200-1200mm	H7V7(120°)	WM-3000±300K NH-4000±300K NH-5000±300K CH-5700±300K	U- Update	E- English	G-Grey

Ordering Information


P/N	Operating Voltage(V)	Luminous Flux(lm)	Power(W)	Color Temp.	CCT(K)	Temp. Classification
Ex-KSF18*600H7V7WM-U-E-G	100-277 AC (141-392 DC)	2268	18	Warm white	3000±300	T6
Ex-KSF18*600H7V7NH-U-E-G		2457	18	Natural white	4000±300	
Ex-KSF18*600H7V7NH-U-E-G		2457	18	Natural white	5000±300	
Ex-KSF18*600H7V7CH-U-E-G		2457	18	Cool white	5700±300	
Ex-KSF36*600H7V7WM-U-E-G		4536	36	Warm white	3000±300	
Ex-KSF36*600H7V7NH-U-E-G		4914	36	Natural white	4000±300	
Ex-KSF36*600H7V7NH-U-E-G		4914	36	Natural white	5000±300	
Ex-KSF36*600H7V7CH-U-E-G		4914	36	Cool white	5700±300	
Ex-KSF48*600H7V7WM-U-E-G		6048	48	Warm white	3000±300	
Ex-KSF48*600H7V7NH-U-E-G		6552	48	Natural white	4000±300	
Ex-KSF48*600H7V7NH-U-E-G		6552	48	Natural white	5000±300	
Ex-KSF48*600H7V7CH-U-E-G		6552	48	Cool white	5700±300	
Ex-KSF36*1200H7V7WM-U-E-G		4536	36	Warm white	3000±300	
Ex-KSF36*1200H7V7NH-U-E-G		4914	36	Natural white	4000±300	
Ex-KSF36*1200H7V7NH-U-E-G		4914	36	Natural white	5000±300	
Ex-KSF36*1200H7V7CH-U-E-G		4914	36	Cool white	5700±300	
Ex-KSF48*1200H7V7WM-U-E-G		6048	48	Warm white	3000±300	
Ex-KSF48*1200H7V7NH-U-E-G		6552	48	Natural white	4000±300	
Ex-KSF48*1200H7V7NH-U-E-G		6552	48	Natural white	5000±300	
Ex-KSF48*1200H7V7CH-U-E-G		6552	48	Cool white	5700±300	
Ex-KSF56*1200H7V7WM-U-E-G		7056	56	Warm white	3000±300	
Ex-KSF56*1200H7V7NH-U-E-G		7644	56	Natural white	4000±300	
Ex-KSF56*1200H7V7NH-U-E-G		7644	56	Natural white	5000±300	
Ex-KSF56*1200H7V7CH-U-E-G		7644	56	Cool white	5700±300	
Ex-KSF72*1200H7V7WM-U-E-G		9072	72	Warm white	3000±300	
Ex-KSF72*1200H7V7NH-U-E-G		9828	72	Natural white	4000±300	
Ex-KSF72*1200H7V7NH-U-E-G		9828	72	Natural white	5000±300	
Ex-KSF72*1200H7V7CH-U-E-G		9828	72	Cool white	5700±300	

Remarks: 1.*Stands for Operating Voltage, including Default -AC-100~277V,A-AC/DC 24~48V,B-DC 10~30V.
2.10-30VDC & 24-48V AC/DC are not suitable for 72W.

Candela Distribution




H7V7(120°)/High Efficacy LED Source




Installation Method


Stanchion Mount:




Ceiling Mount:



Pendant Mount:




Clamp Mount:



Installation Method

Pipe Clamp Mount:



Optional Parts

No.	Installation accessories	Part No.	Picture	Material	Weight(Kg)	QTY	Remark
1	Bracket	BR-SF-U-G		Q235	0.8	2	Ceiling Mount
2	Loop	LO-SF-U-G		Q235	1.2	2	Pendant Mount
3	Pipe Clamp	PCP-SF-U-G		Q235	1.8	2	Pipe clamp
4	Stanchion bracket	SBT-SF-U-G		Q235	2.6	2	Stanchion mount Wall mount (1200mm)
5	Clamp mount	CM-SF-U-G		Q235	3	2	Clamp mount (1200mm)
6	Stanchion bracket	SBT-SF-U-G-T5		Q235	3.4	2	Stanchion mount Wall mount (600mm)
7	Clamp mount	CM-SF-U-G-T5		Q235	3.8	2	Clamp mount (600mm)