




LED Industrial Light

**CE & RoHS Certified LED Floodlight Light in Industrial Area.
Tank Series**

CE RoHS

www.khjled.com



Features And Benefits:

- High efficacy LED Source with long lifespan, L70 > 100,000 hours @ 25°C ambient
- 5-year performance warranty
- Low THD around 10%, Less interference
- 4KV/Line-Line 6KV/Line-Earth
- Robust aluminium housing and strong tempered glass
- Vibration and shock resistant
- Low maintenance
- Dust proof structure design to avoid dust accumulation

Applications:



Cement plants



Warehouse



Factory



Power Generation



Power Transmission



Shipping industry

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.

LED Floodlight

Standard & Certificate:

Certificate:	• CE • RoHS
Executive Standard:	• EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3 • EN 60598-1, EN 60598-2-5, EN 62031, EN 62493 • IEC 62321-4, IEC 62321-5, IEC 62321-6 • IEC 62321-7-1, IEC 62321-7-2, IEC 62321-8

Electrical & Photometric Features:

Luminaire Efficacy:	Max:152lm/W
Lifespan:	>100,000 hours
Operating Voltage:	100-277 VAC,141-392VDC(347-480 VAC,491-679 VDC are optional)
Power:	80W/100W/120W(Single lamp) 160W/200W/240W(Two lamps), 320W/400W/480W(Four lamps)
Frequency:	50/60Hz
Power Factor:	>0.98
THD:	<10%
Insulation Class:	I
Surge Protection:	4KV/6KV
LED Driver:	Over voltage protection/short circuit protection


Mechanical Features:

Weight:	8.3Kg(80W~120W)/15Kg(160W~240W)/32kg(320W~480W)
Size:	332*212*142mm(80W~120W)/332*426*142mm(160W~240W) /671*426*142mm(320W~480W)
Ambient Temperature:	-40℃~+55℃
Connecting Terminals:	3*1.0-4.0mm ² (L+N+PE)
Cable Entries:	2XM20*1.5 (NPT 3/4", M25*1.5 are optional)
Earthing Protection:	M4 (Internal & external earth bolts)
IP Code:	IP66
Enclosure Material:	Aluminium
Enclosure Colour:	Grey RAL7040
Coating:	Epoxy powder coating
Exposed Fastener:	Stainless steel
Protective Cover:	Tempered glass,Stand 7J impact

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.

Production Definition



Ordering information

P/N	Operating Voltage(V)	Luminous Flux(lm)	Power(W)	CRI	Color Temp.	CCT(K)
KTK80**CH-J-E	100-277 VAC (141-392 VDC)	12107	80	80	Cool white	5700K±300K
KTK80**NH-J-E		12107		80	Natural white	5000K±300K
KTK80**NH-J-E		12107		80	Natural white	4000±300k
KTK80**WM-J-E		10896		80	Warm white	3000±300k
KTK100**CH-J-E		14954	100	80	Cool white	5700±300k
KTK100**NH-J-E		14954		80	Natural white	5000±300k
KTK100**NH-J-E		14954		80	Natural white	4000±300k
KTK100**WM-J-E		13458		80	Warm white	3000±300k
KTK120**CH-J-E		17310	120	80	Cool white	5700±300k
KTK120**NH-J-E		17310		80	Natural white	5000±300k
KTK120**NH-J-E		17310		80	Natural white	4000±300k
KTK120**WM-J-E		15579		80	Warm white	3000±300k
KTK160**CH-S2-J-E		22910	160	80	Cool white	5700K±300K
KTK160**NH-S2-J-E		22910		80	Natural white	5000K±300K
KTK160**NH-S2-J-E		22910		80	Natural white	4000±300k
KTK160**WM-S2-J-E		20619		80	Warm white	3000±300k
KTK200**CH-S2-J-E		29145	200	80	Cool white	5700±300k
KTK200**NH-S2-J-E		29145		80	Natural white	5000±300k
KTK200**NH-S2-J-E		29145		80	Natural white	4000±300k
KTK200**WM-S2-J-E		26230		80	Warm white	3000±300k
KTK240**CH-S2-J-E		34136	240	80	Cool white	5700±300k
KTK240**NH-S2-J-E		34136		80	Natural white	5000±300k
KTK240**NH-S2-J-E		34136		80	Natural white	4000±300k
KTK240**WM-S2-J-E		30884		80	Warm white	3000±300k

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.

P/N	Operating Voltage(V)	Luminous Flux(lm)	Power(W)	CRI	Color Temp.	CCT(K)
KTK320**CH-S4-J-E	100-277 VAC (141-392 VDC)	46400	320	80	Cool white	5700±300k
KTK320**NH-S4-J-E		46400		80	Natural white	5000±300k
KTK320**NH-S4-J-E		46400		80	Natural white	4000±300k
KTK320**WM-S4-J-E		41760		80	Warm white	3000±300k
KTK400**CH-S4-J-E		58054	400	80	Cool white	5700±300k
KTK400**NH-S4-J-E		58054		80	Natural white	5000±300k
KTK400**NH-S4-J-E		58054		80	Natural white	4000±300k
KTK400**WM-S4-J-E		52248		80	Warm white	3000±300k
KTK480**CH-S4-J-E		69120	480	80	Cool white	5700±300k
KTK480**NH-S4-J-E		69120		80	Natural white	5000±300k
KTK480**NH-S4-J-E		69120		80	Natural white	4000±300k
KTK480**WM-S4-J-E		62208		80	Warm white	3000±300k


Remarks: 1.The first * stands for Operating Voltage including default -100-277VAC,D-347-480VAC.

2.The second * stands for Candela Distribution including H3V3,H5V5,H6V6.



CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.



Candela Distribution



H3V3(40°)/High efficacy LED Source



H5V5(80°)/High efficacy LED Source



H6V6(120°)/High efficacy LED Source



CE RoHS


CE & RoHS Certified LED Floodlight in Industrial Area.

Installation Method

Stanchion mount / Wall mount

(unit:mm)


360°ROTATION(EVERY15° IS A ROTATION ANGLE)



SBT-TK-SUS316

Single lamp


360°ROTATION(EVERY15° IS A ROTATION ANGLE)



SBT-TK-2-SUS316

Two lamps

360°ROTATION(EVERY15° IS A ROTATION ANGLE)



SBT-TK-4-G


Four lamps

CE RoHS


CE & RoHS Certified LED Floodlight in Industrial Area.

Installation Method


Ceiling mount:



Single lamp



Two lamps



Four lamps

CE RoHS


CE & RoHS Certified LED Floodlight in Industrial Area.

Installation Method

Pole Mount:

(unit:mm)


360°ROTATION(EVERY15° IS A ROTATION ANGLE)



(SBT-TK-SUS316)+(SBT2-F-G)
Single lamp

360°ROTATION(EVERY15° IS A ROTATION ANGLE)

(unit:mm)




(SBT-TK-2-SUS316)+(SBT2-F-G)
Two lamps

Remarks: Pole mount bracket for four lamps needs to be customized.

CE RoHS

CE & RoHS Certified LED Floodlight in Industrial Area.

Optional Parts

No.	Installation Accessories	Part No.	Picture	Material	Weight(Kg)	QTY		Remarks
1	Ceiling Bracket	BR-TK-SUS316		SUS316	0.9	Single lamp	1	
						Two lamps	1	
						Four lamps	1	
2	Stanchion Bracket	SBT-TK-SUS316		SUS316	0.8	1		Single lamp
3	Stanchion Bracket	SBT-TK-2-SUS316		SUS316	1	1		Two lamps
4	Stanchion Bracket	SBT-TK-4-G		Q235	3	1		Four lamps
5	Pole Mount Bracket	(SBT2-F-G) +(SBT-TK-SUS316)		SUS316+Q235	2.4	1		Single lamp
6	Pole Mount Bracket	(SBT2-F-G) +(SBT-TK-2-SUS316)		SUS316+Q235	2.6	1		Two lamps